

DUAL PUMP FACILITY

The special design of the Transcube 'Global' allows fitting of a hand pump as well as an electric pump in the area under the lockable hatch.

© WESTERN 2006 - 1107 - TOG LEAFLET - CANADA

TRANSCUBE GLOBAL OPTIONAL PUMPS AND FITTINGS



15GPM/56LPM electric transfer pump with 12' delivery hose, manual nozzle, 15' power cord.

- 12 Volt #M150S
- 24 Volt # M240S
- 115 Volt # M1115S



Mechanical flow meter 3/4" with gallons or litre display.

- Gallon display # 807C
- Litre Display # 807CLMK



Auto shut off nozzle.

- 3/4" # 11TNL
- 1" # 7TH



Arctic Fuel Delivery Hose. 15', 25' and 50' or custom lengths available.

- 3/4" # 62675
- 1" # 626100



3/4" Semi rotary hand pump (1/4 turn) available as feed line primer w/O.D. or fuel transfer pump with manual nozzle.

- Primer Pump w/Quick Connect #K1P
- Transfer Pump w/12' Hose & Manual Nozzle # K1N



Feed and return assemblies c/w feed, down tube check valve, strainer and return port.

- 1/2" # RN08KT
- 3/4" # RN12KT
- 1" # RN16KT



Engine feed/return hose assembly c/w male/female couplers available in 1/4, 3/8, 1/2, 3/4 and 1". Hose length sized to suit your application.



LIFTING HARNESS

Wire rope or chain c/w self locking safety hooks, and single point top yoke. Available for all Transcube sizes.



SITE TOW TRAILER:

Low speed trailer chassis for ease of manoeuvring on rugged sites.

- 10TCG Trailer # ST1000G
- 20TCG Trailer # ST2000G



CUSTOM SKID OPTIONS

A variety of options to fit your application.

STANDARD COLOUR - CREAM WHITE COLOUR OPTIONS



THE TRANSCUBE GLOBAL RANGE

50TCG - 4700 litres

30TCG - 3000 litres

20TCG - 2000 litres



10TCG - 1000 litres



05TCG - 500 litres

TRANSCUBE GLOBAL SPECIFICATIONS

| MODEL | CAPACITY | | | DIMENSIONS Inches/(mm) | | | WEIGHT LBS/(Kg) | |
|-------|----------|------------|-------------|------------------------|------------------|--------------|------------------|-------------------|
| | LITRES | US GALLONS | IMP GALLONS | LENGTH | WIDTH | HEIGHT | EMPTY | FULL |
| 05TCG | 500 | 132 | 110 | 45 1/4" (1155mm) | 45 1/4" (1155mm) | 33" (838mm) | 965LBS (437KG) | 1901LBS (862KG) |
| 10TCG | 1000 | 264 | 220 | 45 1/4" (1155mm) | 45 1/4" (1155mm) | 52" (1320mm) | 1118LBS (508KG) | 2994LBS (1358KG) |
| 20TCG | 2000 | 528 | 440 | 86 1/4" (2190mm) | 45 1/4" (1155mm) | 52" (1320mm) | 1825LBS (828KG) | 5574LBS (2528KG) |
| 30TCG | 3000 | 792 | 660 | 90 1/2" (2300mm) | 59 1/8" (1500mm) | 52" (1320mm) | 2153LBS (972KG) | 7765LBS (3522KG) |
| 50TCG | 4700 | 1240 | 1035 | 90 1/2" (2300mm) | 90 1/2" (2300mm) | 52" (1320mm) | 3567LBS (1618KG) | 12235LBS (5550KG) |

*WESTERN reserve the right to amend specification without notice.



BattlefieldEquipment.ca | 1-800-RENT-CAT



TRANSCUBE GLOBAL

FOR RAPID, LEGAL, FUEL TRANSPORTATION AND DEPLOYMENT WORLDWIDE!

YOUR DOUBLE WALLED US DOT/ TRANSPORT CANADA APPROVED MOBILE IBC (Intermediate Bulk Container) FOR TRANSPORT OF DIESEL FUEL; BUILT, TESTED AND CERTIFICATED TO UN REQUIREMENTS

AVAILABLE IN
500 Litres - 4700 Litres
132 US Gallons - 1240 US Gallons
110 Imp Gallons - 1035 Imp Gallons



BattlefieldEquipment.ca | 1-800-RENT-CAT

ENVIRONMENTALLY AWARE

In compliance with environmental protection measure, the Transcube 'Global' features a

CONTAINMENT TANK CAPACITY OF 110% of the inner tank.


All connection ports, pumps, hoses, nozzles, etc. are housed within this containment area.



MULTIPLE FUELING

The Transcube 'Global' has the capacity to run feed/return lines up to 3 diesel engines at a time.

THE TRANSCUBE 'GLOBAL' FEATURES AND BENEFITS



BAFFLED INNER TANK FOR TRANSPORTING

Internal baffles to prevent surge during transport.

REDUCING YOUR STORAGE NEEDS

The Transcube 'Global' is approved for stacking 2 high full and 3 high empty, helping to reduce your storage space requirements.



INNOVATIVE CORNER BRACKETS

Tank can be both lifted and secured using the innovative combination lifting eye / tie down corner bracket.



GALVANIZED FRAME WORK

Galvanized corner brackets, framework, hatch and manway cover for added protection for tank and paintwork.



FUEL LINE SECURITY FEATURE

Fuel line feed and return hoses through letter box opening means the lid can be left closed and locked even when in use, providing extra security.



MANEUVERABILITY

Forklift pockets are on all 4 sides for ease of maneuvering.

MAINTAINING STANDARDS

The Transcube 'Global' is fabricated with 11 gauge (3mm) mild steel to comply with United Nations 'Standardized Means of Containment' guidelines.

Standard fitting includes 3" fusible fill port, contents gauge, pressure/vacuum vents, 1" pump feed connection, 1/2" feed and return line connections for generator, and inspection manhole.

QUALITY STANDARD



USER FRIENDLY FEATURE

Equipped with removable and flexible dip pipes for ease of maintenance and customized set up.



OPTIMUM LOGISTICS

- You can transport:
- 10TCG x 56 units
 - 20TCG x 28 units
 - 30TCG x 20 units
 - 50TCG x 14 units on a 53' deck or 'high cube dry van'.

TRANSPORTABLE

The Transcube 'Global' range complies with the stated code:

'ALL FUEL TANKS (450 LITRES OR GREATER) MUST COMPLY WITH US/DOT and or TRANSPORT CANADA REQUIREMENTS (TDG Reg. 5.6b) and UNITED NATIONS (INTERMEDIATE BULK CONTAINER) STANDARDS'.



UN COMPLIANT



INNOVATIVE DESIGN

90½" (2.3m) total length on 20TCG and 30TCG models allows transportation across truck bed, inside ISO shipping containers, or in standard dry vans.

The optimal height of 52" allows for stacking inside high cube containers and dry vans, and is a comfortable working height during use.



BattlefieldEquipment.ca | 1-800-RENT-CAT